

PRINT DATA



- ☐ Data format
- ☒ Bleed
- ☐ Final format
- ☐ Safety distance



JPG, TIFF only for image files



PDF files



CMYK or greyscales, 8 Bits/Channel

RGB colors are automatically converted to CMYK.
Special colors must be named correctly or converted to CMYK colors (approximate values from the manufacturer)
Color profile: ISO Coated v2 (ECI), www.eci.org

Dense Black

Dense Black: C = 87%, M = 78%, Y = 65% und K = 100%



72 dpi resolution for pictures

In a ratio of 1:1 at least 72 dpi
In a ratio of 1:10 at least 720 dpi

Texts and logos in vectore files or 100 dpi

Aa

All fonts must be converted to paths or be embedded

At least 0.3" font height



Do not apply crop, bleed or registration marks



0.5" safety margin

To ensure that no important information is cropped, a safety margin of at least 0.5" from the final format must be maintained.



0.5" bleed

The bleed is the area outside the final format that is sewn to the rubber lip after printing. To avoid white stripes, it must be 0.5" all round per side length. The graphics in the print file must fill the entire bleed area.



End format

Data format

39.37" x 39.37"

40.37" x 40.37"

33" x 96"

34" x 97"

39" x 96"

40" x 97"

73" x 96"

74" x 97"

78" x 96"

79" x 97"

111" x 96"

112" x 97"

117" x 96"

118" x 97"